

uniarch  
Powered by uniview Tech.

# PRICE LIST

---

1403 . 03. 10

[WWW.DORBINCITY.COM](http://WWW.DORBINCITY.COM)  
0910 317 9 319 & 02166563506

**Dcity**  
دوربین سیتی

01



IPC-B122-APF40

2.0MP Mini Fixed Bullet Network Camera, Built-in MIC

- ◆ Sensor: 1/2.8" progressive scan, CMOS
- ◆ Lens: 4.0mm@F2.1, Angle of view: 87.5°
- ◆ Ultra 265 / H.265 / H.264
- ◆ Frame Rate: Main Stream: 1080P(1920\*1080), Max 25fps
- ◆ Digital Defog, DWDR, HLC, BLC, OSD, Privacy Mask, ROI, Motion Detection, 2D/3D DNR, ONVIF
- ◆ Built in MIC
- ◆ IR anti-reflection window to increase the infrared transmittance
- ◆ IR Range: UP to 30m
- ◆ Ingress Protection: IP67 / Plastic, PoE



25.300.000 IR/rials

02



IPC-T122-APF28

2.0MP Fixed Turret Network Camera

- ◆ Sensor: 1/2.8" progressive scan, CMOS
- ◆ Lens: 2.8mm @ F2.1, Angle of view: 106.7°
- ◆ Ultra 265 / H.265 / H.264
- ◆ Frame Rate: Main Stream: 1080P(1920\*1080), Max 25fps
- ◆ Digital Defog, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection
- ◆ 2D/3D DNR, 3-Axis, ONVIF
- ◆ Built in MIC
- ◆ IR Range: UP to 30m
- ◆ Ingress Protection: IP67, Plastic, PoE



25.300.000 IR/rials

03



IPC-B222-APF40

2.0MP Fixed Bullet Network Camera, Built-in MIC

- ◆ Sensor: 1/3" progressive scan, CMOS
- ◆ Lens: 4.0mm@F2.1, Angle of view: 80°
- ◆ H.265 / H.264, U-Code
- ◆ Frame Rate: Main Stream: 1080P(1920\*1080), Max 25fps
- ◆ Digital Defog, DWDR, HLC, BLC, OSD, Privacy Mask, ROI, Motion Detection, 2D/3D DNR, ONVIF
- ◆ Built in MIC
- ◆ IR anti-reflection window to increase the infrared transmittance
- ◆ IR Range: Up to 60m
- ◆ Ingress Protection: IP67, Plastic and Metal, PoE



32.000.000 IR/rials

04



IPC-D122-PF28

2.0MP Fixed Vandal Dome Network Camera

- ◆ Sensor: 1/2.9" progressive scan, CMOS
- ◆ Lens: 2.8mm @ F2.0, Angle of view: 107°
- ◆ Ultra 265 / H.265 / H.264
- ◆ Frame Rate: Main Stream: 1080P(1920\*1080), Max 25fps
- ◆ Digital Defog, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection
- ◆ 2D/3D DNR, 2-Axis, ONVIF
- ◆ IR anti-reflection window to increase the infrared transmittance
- ◆ IR Range: Up to 30m
- ◆ Ingress Protection: IP67, Plastic, Vandal Resistant: IK10, PoE



32.600.000 IR/rials

05



IPC-B213-APF40W

3.0MP HD Fixed Dual-light Bullet Network Camera

- ◆ Sensor: 1/2.8", 3.0 Megapixel, CMOS
- ◆ Lens: 4.0mm @ F2.0, Angle of view: 89.0°
- ◆ Ultra 265 / H.265 / H.264, U-Code
- ◆ Frame Rate: Main Stream: 3MP(2304\*1290), Max 25fps, 1080P(1920\*1080), Max 30fps
- ◆ Digital Defog, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection
- ◆ 2D/3D DNR, ONVIF
- ◆ Basic Detection: Motion Detection, Humanbody Detection, Audio Detection
- ◆ Built in MIC
- ◆ White Light Range: Up to 30m (98ft)
- ◆ Smart IR, IR Range: Up to 50m
- ◆ Ingress Protection: IP67, Plastic, With Bracket



50.700.000 IR/rials

موجودی استعلام شود

06



IPC-B124-APF40

#### 4.0MP Fixed Bullet Network Camera

- ◆ Sensor: 1/3", progressive scan, CMOS
- ◆ Lens: 4.0mm @F2.1, Angle of view: 79.0°
- ◆ Ultra 265 / H.265 / H.264
- ◆ Frame Rate: Main Stream: 4MP(2560\*1440), Max 20fps; 1080P (1920\*1080), Max 20fps
- ◆ Digital Defog, DWDR, HLC, BLC, OSD, Privacy Mask, ROI, Motion Detection,
- ◆ 2D/3D DNR, ONVIF
- ◆ Built in MIC
- ◆ IR anti-reflection window to increase the infrared transmittance
- ◆ Smart IR, IR Range: UP to 30m
- ◆ Ingress Protection: IP67, Plastic, PoE



42.200.000 IR/rials

07



IPC-T124-APF28

#### 4.0MP Fixed Turret Network Camera

- ◆ Sensor: 1/3" progressive scan, CMOS
- ◆ Lens: 2.8mm @F2.1, Angle of view: 97°
- ◆ Ultra 265 / H.265 / H.264
- ◆ Frame Rate: Main Stream: 4MP(2560\*1440), Max 20fps; 3MP (2304\*1296), Max 20fps; 1080P (1920\*1080), Max 30fps
- ◆ Digital Defog, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection
- ◆ 2D/3D DNR, 3-Axis, ONVIF
- ◆ Built in MIC
- ◆ IR anti-reflection window to increase the infrared transmittance
- ◆ Smart IR, IR Range: Up to 30m
- ◆ Ingress Protection: IP67, Plastic, PoE



43.500.000 IR/rials

ناموجود

08



IPC-D114-PF28

#### 4.0MP Fixed Dome Network Camera

- ◆ Sensor: 1/2.7", progressive scan, CMOS
- ◆ Lens: 2.8mm @F2.0, Angle of view: 112.7°
- ◆ Ultra 265 / H.265 / H.264, MJPEG
- ◆ Frame Rate: Main Stream: 4MP(2560\*1440), Max 20fps; 1080P (1920\*1080), Max 20fps
- ◆ Digital Defog, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection
- ◆ 2D/3D DNR, ONVIF, 2-Axis
- ◆ IR anti-reflection window to increase the infrared transmittance
- ◆ Smart IR, IR Range: Up to 30m
- ◆ Ingress Protection: IP67, Plastic, Vandal Resistant IK10, PoE



42.500.000 IR/rials

ناموجود

09



IPC-D124-PF28

#### 4.0MP Fixed Dome Network Camera

- ◆ Sensor: 1/3" progressive scan, CMOS
- ◆ Lens: 2.8mm @F2.1, Angle of view: 97°
- ◆ Ultra 265 / H.265 / H.264
- ◆ Frame Rate: Main Stream: 4MP(2560\*1440), Max 20fps; 3MP (2304\*1296), Max 20fps; 1080P (1920\*1080), Max 30fps
- ◆ Digital Defog, DWDR, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection
- ◆ 2D/3D DNR, ONVIF, 2-Axis
- ◆ IR anti-reflection window to increase the infrared transmittance
- ◆ Smart IR, IR Range: Up to 30m
- ◆ Ingress Protection: IP67, Plastic, Vandal Resistant IK10, PoE



42.500.000 IR/rials

ناموجود

10



IPC-B314-APKZ

4.0MP HD Motorized Bullet Network Camera

- ◆ Sensor: 1/2.7" progressive scan, CMOS
- ◆ Lens: 2.8 ~ 12mm @F1.8, Angle of view: 102.79° ~ 30.86°
- ◆ Ultra 265 / H.265 / H.264, MJPEG
- ◆ Frame Rate: Main Stream: 4MP(2560\*1440), Max 25fps; 3MP (2304\*1296), Max 30fps; 1080P(1920\*1080), Max 30fps
- ◆ Digital Defog, WDR120db, HLC, BLC, OSD, Privacy Mask, ROI, Motion Detection
- ◆ 2D/3D DNR, ONVIF
- ◆ Behavior Detection: motion detection, tampering alarm, audio detection, human body detection
- ◆ Built in MIC, Reset Button
- ◆ Edge Storage: Micro SD, up to 256GB, ANR
- ◆ IR anti-reflection window to increase the infrared transmittance
- ◆ Smart IR, IR Range: Up to 50m ◆ Ingress Protection: IP67, Surge Protection, Plastic, PoE



92.000.000 IR/rials

11



IPC-D314-APKZ

4.0MP Motorized Vandal-resistand IR Network Dome Camera

- ◆ Sensor: 1/2.7" progressive scan, CMOS
- ◆ Lens: 2.8 ~ 12mm @F1.8, Angle of view: 102.79° ~ 30.86°
- ◆ Ultra 265 / H.265 / H.264, MJPEG
- ◆ Frame Rate: Main Stream: 4MP(2560\*1440), Max 25fps; 3MP (2304\*1296), Max 25fps; 1080P (1920\*1080), Max 30fps
- ◆ Digital Defog, WDR120db, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection
- ◆ 2D/3D DNR, ONVIF, 3-Axis
- ◆ Behavior Detection: motion Detection, Tampering Alarm, Audio Detection, Human body Detection
- ◆ Edge Storage: Micro SD, up to 256GB, ANR ◆ Built in MIC, Reset Button
- ◆ IR anti-reflection window to increase the infrared transmittance
- ◆ Smart IR, IR Range: Up to 30m
- ◆ Ingress Protection: IP67, Surge Protection, Plastic, Vandal Resistant IK10, PoE



92.000.000 IR/rials

12



IPC-P213-AF40KC

3.0MP HD Dual Light Network PT Camera

- ◆ Sensor: 1/2.8" progressive scan, 3.0MP, CMOS
- ◆ Lens: 4mm @F1.6, Angle of view: 111.3°
- ◆ Frame Rate: 3MP(2304\*1296)@20fps
- ◆ Ultra 265 / H.265 / H.264
- ◆ Intelligent: Line Crossing Detection, Intrusion Detection
- ◆ Support DWDR, HLC, BLC, D-Defog, OSD, Privacy mask, ROI, Motion Detection
- ◆ 2D/3D DNR, ONVIF
- ◆ Built-in MIC & Speaker, support two-way audio
- ◆ Edge Storage: Micro SD, up to 256GB, ANR
- ◆ Smart IR, Up to 30 m (98 ft) IR and 30m (98 ft) warm light distance
- ◆ Self-Contained Bracket, Support two kinds of mounting
- ◆ Ingress Protection: IP66, Surge Protection, Plastic, PoE



"The front face is made of grapheme, which has better heat dissipation and more environmental protection"

78.000.000 IR/rials

13



IPC-P1E5-AX4PKC

### 5.0MP Light-hunter Active Deterrence Mini PTZ Camera

- ◆ Sensor: 1/2.7" progressive scan, CMOS
- ◆ Lens: 2.8 ~ 12mm @F1.6, Angle of view: 30.6° ~ 104.1°
- ◆ Min. Illumination: Colour: 0.003 lux (F1.6, AGC ON) 0 lux with IR
- ◆ Ultra 265 / H.265 / H.264, MJPEG
- ◆ Frame Rate: 5MP (2880\*1620), Max 30fps; 4MP (2560\*1440), Max 25fps; 3MP (2304\*1296), Max 25fps; 2MP (1920\*1080), Max 30fps;
- ◆ Digital Defog, WDR 120db, HLC, BLC, OSD, Privacy Mask, ROI, Motion Detection
- ◆ 2D/3D DNR, ONVIF
- ◆ Intelligent Cross Line, Intrusion, Enter Area Detection, Leave Area Detection
- ◆ Motion Detection, Tampering Alarm, Audio Detection, Two-way Audio
- ◆ Edge Storage: Micro SD, up to 256GB, ANR
- ◆ Built-in Mic, Built-in Speaker, Alarm Light, Reset Button
- ◆ IR anti-reflection window to increase the infrared transmittance
- ◆ Smart IR, IR Range: Up to 50m, Warm Light Range to 10m
- ◆ Ingress Protection: IP66, PoE



182.000.000 IR/rials

موجودی استعلام شود

14



IPC-P413-X20

### 3.0MP 20X Network PTZ Dome Camera

- ◆ Sensor: 1/2.8" progressive scan, CMOS
- ◆ Lens: 5 ~ 100mm @F1.5 ~ F3.8, Angle of view: 63.06° ~ 4.54°
- ◆ Min. Illumination: Colour: 0.003 Lux
- ◆ Optical Zoom: 20X
- ◆ H.265 / H.264, MJPEG
- ◆ Frame Rate: Main Stream: 3MP(2304\*1296), Max 30fps
- ◆ Digital Defog, WDR 120db, HLC, BLC, OSD, Privacy mask, ROI, Motion Detection
- ◆ 2D/3D DNR, ONVIF
- ◆ Intelligent Line Crossing Detection, Intrusion Detection, Leave Area Detection, Face Capture, People Counting, Crowd Density
- ◆ Motion Detection, Auto Tracking, Two-way Audio
- ◆ Edge Storage: Micro SD, up to 256GB, ANR
- ◆ Reset Button
- ◆ IR anti-reflection window to increase the infrared transmittance
- ◆ Smart IR, IR Range: Up to 100m
- ◆ Ingress Protection: IP66, Plastic, PoE & PoE+
- ◆ NO BRACKET



247.000.000 IR/rials

16



NVR-104E2

4 CH. 1 SATA HDD Network Video Recorder

- ◆ IP Video Input 4 CH.
- ◆ Decoding format: Ultra 265 / H.265 / H.264
- ◆ Recording Resolution: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF/QCIF
- ◆ Live view/Play back: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆ Hard Disk: 1 SATA Interface, Up to 6TB
- ◆ Network Interface : 1RJ45 10M/100M self-adaptive Ethernet Interface
- ◆ Support 1 CH. HDMI, 1 CH. VGA
- ◆ USB Interface : 2x Rear Panel
- ◆ Third-party IP camera supported with ONVIF conformance: Profile S, Profile G, Profile T
- ◆ Incoming/Outcoming Bandwidth: 64/32Mbps



46.700.000 IR/rials

17



NVR-110E2

10 CH. 1 SATA HDD Network Video Recorder

- ◆ IP Video Input 10CH.
- ◆ Decoding Format: Ultra 265 / H.265 / H.264
- ◆ Recording Resolution: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆ Live view/Play back: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆ Hard Disk: 1 SATA Interface, Up to 6TB
- ◆ Network Interface : 1RJ45 10M/100M self-adaptive Ethernet Interface
- ◆ Support 1 CH. HDMI, 1 CH. VGA
- ◆ Audio Output 1 CH. 3.5mm
- ◆ USB Interface : 2x Rear Panel
- ◆ Third-party IP camera supported with ONVIF conformance: Profile S, Profile G, Profile T
- ◆ Incoming/Outcoming Bandwidth: 64/32Mbps



56.200.000 IR/rials

18



NVR-116E2

16 CH. 1 SATA HDD Network Video Recorder

- ◆ IP Video Input 16 CH.
- ◆ Decoding format: Ultra 265/H.265/H.264
- ◆ Recording Resolution: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
- ◆ Live view/Play back: 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
- ◆ Hard Disk: 1 SATA Interface, Up to 6TB
- ◆ Network Interface: 1 RJ45 10M/100M self-adaptive Ethernet Interface
- ◆ Support 1 CH. HDMI, 1 CH. VGA
- ◆ Audio Output 1 CH. 3.5mm
- ◆ USB Interface : 2x Rear Panel
- ◆ Incoming/Outcoming Bandwidth: 64/32Mbps



67.500.000 IR/rials

موجودی استعلام شود

19



NVR-216S2

16 CH. 2 SATA HDDs Network Video Recorder

- ◆ IP Video Input 16 CH.
- ◆ Decoding format: Ultra 265 / H.265 / H.264
- ◆ Recording Resolution: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆ Live view/Play back: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆ Hard Disk: 2 SATA Interfaces, Up to 6TB
- ◆ Network Interface : 1RJ45 10M/100M/1000M self-adaptive Ethernet Interface
- ◆ Support 1 CH. HDMI, 1 CH. VGA
- ◆ Audio Output 1 CH. RCA
- ◆ USB Interface : 1X Rear Panel & 1X Front Panel
- ◆ Incoming/Outcoming Bandwidth: 160/96Mbps
- ◆ VCA by Camera: Intrusion, CrossLine Detection, Enter / Leave Area Detection



89.000.000 IR/rials

موجودی استعلام شود

20



ITR-NV322-4K  
(ITR, UNIARCH OEM)

32 CH. 2 SATA HDDs Network Video Recorder

- ◆ IP Video Input: 32 CH.
- ◆ Decoding format: Ultra 265 / H.265 / H.264
- ◆ Recording Resolution: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆ Live view/Play back: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆ Hard Disk: 2 SATA Interfaces, Up to 8TB
- ◆ Network Interface : 2RJ45 10M/100M/1000M self-adaptive Ethernet Interface
- ◆ Support 1 CH. HDMI 4K, 1 CH. VGA
- ◆ Audio Output: 1 CH. RCA
- ◆ USB Interface : 1x Rear Panel & 1x Rear Panel (USB 3.0) & 1x Front Panel
- ◆ Incoming/Outcoming Bandwidth: 160/64Mbps
- ◆ ANR Support
- ◆ 8CH. VCA Detection by Camera: Intrusion, Line Crossing Detection, Enter/Leave Area Scene Change, Left / Removed Object Detection, Auto Tracking, People Counting, Crowd Density, Humanbody Detection



152.000.000 IR/rials

موجودی استعلام شود

21



NVR-104E2-P4

4 CH. 1 SATA HDD PoE Network Video Recorder

- ◆ IP Video Input: 4 CH.
- ◆ Decoding Format: Ultra 265/H.265/H.264
- ◆ Recording Resolution: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF/QCIF
- ◆ Live view/Play back: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆ Hard Disk: 1 SATA Interface, Up to 6 TB
- ◆ Network Interface: 1 RJ45 10M/100M self-adaptive Ethernet Interface
- ◆ PoE: 4 RJ45 10M/100M self-adaptive Ethernet Interface
- ◆ Support 1 CH. HDMI, 1 CH. VGA
- ◆ USB Interface: 2x Rear Panel
- ◆ Incoming/Outcoming Bandwidth: 40/40Mbps



76.000.000 IR/rials

ناموجود

22



NVR-108E2-P8

8 CH. 1 SATA HDD PoE Network Video Recorder

- ◆ IP Video Input: 8 CH.
- ◆ Decoding Format: Ultra 265/H.265/H.264
- ◆ Recording Resolution: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF/QCIF
- ◆ Live view/Play back: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆ Hard Disk: 1 SATA Interface, Up to 6 TB
- ◆ Network Interface: 1 RJ45 10M/100M self-adaptive Ethernet Interface
- ◆ PoE: 8 RJ45 10M/100M self-adaptive Plug & Play Ethernet Interface
- ◆ Audio Output: 1 CH. RCA
- ◆ Support 1 CH. HDMI, 1 CH. VGA
- ◆ USB Interface: 2x Rear Panel
- ◆ Incoming/Outcoming Bandwidth: 50/40Mbps



114.000.000 IR/rials

ناموجود

23



NVR-216S-P16

16 CH. 2 SATA HDDs PoE Network Video Recorder

- ◆ IP Video Input: 16 CH.
- ◆ PoE Income: 16 CH.
- ◆ Decoding format: Ultra 265/H.265/H.264
- ◆ Recording Resolution: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF/QCIF
- ◆ Live view/Play back: 8MP/5MP/3MP/1080P/960P/960H/D1/2CIF/CIF
- ◆ Hard Disk: 2 SATA Interfaces, Up to 10 TB
- ◆ ANR Technology to enhance the storage reliability when the network is disconnected
- ◆ Network Interface: 1 RJ45 10M/100M/1000M self-adaptive Ethernet Interface
- ◆ PoE: 16 independent 100Mbps PoE network interfaces
- ◆ Audio Output: 1 CH. RCA
- ◆ Support 1 CH. HDMI, 1 CH. VGA
- ◆ Alarm in: 4 CH. Alarm Out 1 CH.
- ◆ USB Interface: 2x Front and Rear Panel
- ◆ Incoming/Outcoming Bandwidth: 160/96Mbps



220.000.000 IR/rials

ناموجود

24

**NEW PRODUCT**



XVR-104G3

**4 CH. 1 SATA HDD Digital Video Recorder**

- ◆ Video compression : H.264/H.265
- ◆ Live : - 5MP@ 20fps
- ◆ Playback : 5MP Lite@12fps/1080P@15fps
- ◆ Analog video input : 4CH (AHD) With 2CH (IP)
- ◆ OR Only IP up to 6CH (IP)
- ◆ Audio input : 1-ch
- ◆ HDMI / VGA
- ◆ Hard disk SATA : 1 SATA interface Up to 8 TB
- ◆ input Support : IP, AHD, TVI, CVI, CVBS
- ◆ Mobile App : Guard viewer
- ◆ pass: 123456



36.500.000 IR/rials

25

**NEW PRODUCT**



XVR-108G3

**8 CH. 1 SATA HDD Digital Video Recorder**

- ◆ Video compression : H.264/H.265
- ◆ Live : 5MP@12fps-1080P 30fps
- ◆ Playback : 5M-N@6fps/1080N@12fps
- ◆ Analog video input : 8CH (AHD) WITH 4CH (IP)
- ◆ OR Only IP up to 8CH (IP)
- ◆ Audio input : 1-ch
- ◆ HDMI / VGA
- ◆ Hard disk SATA : 1 SATA interface Up to 8 TB
- ◆ input Support : IP, AHD, TVI, CVI, CVBS
- ◆ Mobile App : Guard viewer
- ◆ pass: 123456



49.000.000 IR/rials

26

**NEW PRODUCT**



XVR-116G3

**16 CH. 1 SATA HDD Digital Video Recorder**

- ◆ Video compression : H.264/H.265
- ◆ Live : 5MP@ 12fps-1080P 30fps
- ◆ Playback : 5M-N@6fps/1080P@12fps
- ◆ Analog video input : 16CH (AHD) With 8CH (IP)
- ◆ OR Only IP up to 16CH (IP)
- ◆ Audio input : 1-ch
- ◆ HDMI / VGA
- ◆ Hard disk SATA : 1 SATA interface Up to 8 TB
- ◆ input Support : IP, AHD, TVI, CVI, CVBS
- ◆ Mobile App : Guard viewer
- ◆ pass: 123456



87.000.000 IR/rials